

A CONTROL METHOD AND CIRCUIT FOR USING A
HETEROJUNCTION BIPOLAR TRANSISTOR POWER AMPLIFIER IN A ZERO
INTERMEDIATE FREQUENCY ARCHITECTURE TRANSMITTER
CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based on French Patent Application No. 00 11 117 filed August 31, 2000, the disclosure of which is hereby incorporated by reference thereto in its entirety, and the priority of which is hereby claimed under 35 U.S.C. §119.

BACKGROUND OF THE INVENTION

Field of the invention

10 The present invention relates to controlling the amplification of signals transmitted by mobile radiocommunication terminals, especially when using heterojunction bipolar transistor power amplifiers.

Description of the prior art

15 To provide sufficient power during the sending phase, the signal sent by a terminal such as a mobile telephone must be amplified.

 To this end terminals include a power amplifier receiving an input power and delivering an amplified output power, the amplification depending on a control voltage fed to the amplifier.

20 Some power amplifiers using the heterojunction bipolar transistor (HBT) technology are more efficient and much smaller than power amplifiers using other technologies.

 In some cases the transmission architecture adopted by mobile terminal manufacturers is a zero intermediate frequency architecture. In this type of architecture, which reduces cost and size, the amplitude conversion related to
25 amplification (referred to as AM/AM conversion) is a very important parameter. Spectrum degradation associated with AM/AM conversion is critical in a zero intermediate frequency architecture.

30 The degradation is very high at low amplifier output powers in a power amplifier using heterojunction bipolar transistors because the amplifier receives high input powers.

 This being so, an object of the present invention is to palliate these drawbacks by proposing a method and a circuit enabling use of a power amplifier using heterojunction bipolar transistors in a zero intermediate frequency transmission architecture that reduces observable spectrum degradation.

SUMMARY OF THE INVENTION

To this end, the invention provides a method of controlling the power delivered by a heterojunction bipolar transistor power amplifier receiving an input power and delivering an amplified output power in a zero intermediate frequency architecture, the method including a step of detecting the output power and varying a control voltage of the power amplifier by means of a control loop and a step of varying the input power level of the power amplifier.

In an advantageous embodiment the input power is reduced if the output power is less than a predetermined limit value.

The invention also provides a circuit for controlling the power emitted by a heterojunction bipolar transistor power amplifier receiving an input power and delivering an amplified output power in a zero intermediate frequency architecture, the circuit including means for detecting the output power and varying a control voltage of the power amplifier and means for varying the input power of the power amplifier.

The means for varying the input power of the power amplifier are preferably adapted to reduce it if the output power is below a predetermined limit value.

The means for varying the input power of the power amplifier advantageously include a variable attenuator.

In one particular embodiment the control circuit includes a variable gain pre-amplifier.

The invention further provides a radiocommunication terminal including a power control circuit according to the invention.

The invention will be better understood in the light of the following description, which relates to an illustrative and non-limiting embodiment of the invention and is given with reference to the appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram showing the evolution of the output power of a power amplifier as a function of the input power.

Figure 2 is a diagrammatic representation of a device for implementing the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Figure 1 is a diagram representing the output power P_{out} of a power amplifier as a function of its input power P_{in} .

The figure 1 diagram shows various curves corresponding to the evolution

of the output power P_{out} as a function of the input power P_{in} for various values of the control voltage V_C (V_{C1} through V_{C4} , in decreasing order) fed to the power amplifier.

5 The output power P_{out} of a power amplifier is varied by varying the control voltage V_C at constant input power P_{in} .

In the case of mobile radiocommunication terminals, for example, a power pre-amplifier provides a constant input power P_{in} to a power amplifier delivering an output power P_{out} . The level of the output power P_{out} is therefore varied by means of the control voltage V_C at constant input power P_{in} .

10 The figure 1 diagram shows a first area A corresponding to linear operation of the power amplifier and a second area B corresponding to non-linear operation of the power amplifier.

The working area routinely used in the field of mobile radiocommunications is located around the input power P_{in1} shown in figure 1. The optimal efficiency of the power amplifier is obtained in this area, where its operation is non-linear.

15 However, with this method of varying the output power P_{out} , by varying the control voltage V_C , AM/AM conversion is degraded if the control voltage V_C is reduced to obtain a lower output power P_{out} .

In this case the method according to the invention modifies the input power P_{in} if the necessary output power P_{out} becomes too low.

If the output power P_{out} required for correct operation of the terminal is reduced, the control voltage V_C falls to the extent that AM/AM conversion, an important parameter in zero intermediate frequency architectures, is degraded excessively.

25 Shifting the input power P_{in} from the value P_{in1} to the lower constant value P_{in2} for the same output power P_{out4} changes the control voltage V_C from the value V_{C4} to the significantly higher value V_{C1} . The power amplifier then operates in linear mode, which, given the low output power level, does not compromise efficiency.

30 Figure 2 is a diagrammatic representation of a circuit adapted to implement the method of the invention.

The circuit includes a power amplifier 1 receiving an input power P_{in} and delivering an amplified output power P_{out} to an antenna 2 transmitting radio signals from the terminal.

35 The input power P_{in} comes from a pre-amplifier 3 itself receiving on its input side an input power P_1 from a circuit known in the art, not shown. The power

pre-amplifier 3 delivers a power P2 which, after passing through a filter 4 that is also known in the art, provides the input power Pin feeding the power amplifier 1.

5 The device also includes a control loop for the power amplifier 1 including means 5 for detecting the output power Pout and varying the control voltage V_c of the power amplifier 1.

The means 5, which are known in the art, vary the output power Pout by varying the level of the control voltage V_c for constant input power Pin.

The circuit further includes means 6 for varying the input power Pin of the power amplifier 1.

10 The means 6 are adapted to reduce the output power P2 and therefore the input power Pin in accordance with the necessary output power level Pout by acting directly on the power pre-amplifier 3.

To this end, the power pre-amplifier 3 can be a variable gain power pre-amplifier, for example. In a different embodiment the means 6 for controlling and
15 varying the input power Pin can also include a variable attenuator for varying the input power P1 of the power pre-amplifier 3. A variable attenuator is an attenuator whose voltage and current are controlled so that it has a variable attenuation value. Accordingly, below a predetermined output power Pout programmed in the control means 6, for example, the input power Pin of the heterojunction bipolar transistor
20 power amplifier 1 is reduced so that the control voltage V_c of the power amplifier 1 can be increased.

Above the predetermined value of the output power Pout, the device continues to operate in accordance with the method described with reference to the prior art. Accordingly, for sufficiently high values of the output power Pout, the level
25 of the output power Pout is controlled only by the means 5 for varying the control voltage V_c .

The invention makes it possible to use heterojunction bipolar transistor power amplifiers, whose compactness and efficiency are significantly improved compared to those of power amplifiers using other technologies, in a zero
30 intermediate frequency architecture.

Moreover, the operating time between changing or charging the battery of a radiocommunication terminal equipped with the above kind of device using the method according to the invention is greatly increased, being in direct relation to the power demand of the power amplifier 1 of the terminal.